



Part number (example)		DN-19 SRV-42U-8-N-1	DN-19 SRV-42U-8-D
Series		Unique	Dynamic Basic
Standard sizes	Height units (U)	26U, 32U, 36U, 42U, 47U	26U, 32U, 36U, 42U, 47U
	Width (mm)	600, 800	600, 800
	Depth (mm)	1000, 1200	1000
Shipping style	Shipping style	Mounted	Mounted
Front door	Style (800 mm width cabinets)	Steel with 70% perforation, single opening, curved	Steel with 70% perforation, single opening
	Style (600 mm width cabinets)	Steel with 70% perforation, single opening, curved	Steel with 70% perforation, single opening
	Locking	Pivot lever with lock, ready for profile-half cylinder (adapter included), 4-point-locking	Pivot lever with lock
	Opening angle	230°	120°
Rear door	Style (800 mm width cabinets)	Steel with 70% perforation, double opening	Steel with 70% perforation, single opening
	Style (600 mm width cabinets)	Steel with 70% perforation, double opening	Steel with 70% perforation, single opening
	Locking	Pivot lever with lock, ready for profile-half cylinder (adapter included), 3-point-locking	Pivot lever with lock
	Opening angle	230°	120°
Side panels	Side panels	Detachable with snap-in latches, lockable, horizontally devided (from 42U)	Detachable, lockable
Fan area in roof	Fan area in roof	Special construction for fan unit installation	Punched-out holes
	Fan area cover	Top cover (lid) which can be unmounted, perforated	\otimes
Vertical cable ducts	Vertical cable ducts	\otimes	\otimes
Cable entry in base	Style (800 mm + 600 mm width cabinets)	Cut-out with sliding cover as well as cable brush entry in rear side	Cut-out with screwed cover
	Style (800 mm width cabinets)	Additional cable entry brushes left & right	Additional punched out cable entries with plastic covers left & right
Cable entry in top	Style (800 mm + 600 mm width cabinets)	\otimes	\otimes
	Style (800 mm width cabinets)	Cable entry brushes left & right	Punched out cable entries with plastic covers left & right
Load capacity of 19" rails	Load capacity of 19" rails	1000 kg	600 kg
Levelling feet / castors	Levelling feet / castors	Levelling feet + castors	Levelling feet

All brand names and logos that are mentioned are trademarks or registered trademarks of the respective owners. The right to delivery is reserved. All information is provided without guarantee. We assume no liability for printing errors. The right to delivery is reserved. All information is provided without guarantee. We assume no liability for printing errors. The right to delivery is reserved. All information is provided without guarantee. We assume no liability for printing errors. The right to delivery is reserved. All information is provided without guarantee. We assume no liability for printing errors. The right to delivery is reserved. All information is provided without guarantee. We assume no liability for printing errors. The right to delivery is reserved. All information is provided without guarantee. We assume no liability for printing errors. The right to delivery is reserved. All information is provided without guarantee. We assume no liability for printing errors. The right to delivery is reserved. All information is provided without guarantee. We assume no liability for printing errors. The right to delivery is reserved. All information is provided without guarantee. We assume no liability for printing errors. The right to delivery is reserved. All information is provided without guarantee. We assume no liability for printing errors. The right to delivery is reserved. All information errors are printing errors. The right to delivery is reserved. All information errors are printing errors. The right to delivery is reserved. All information errors are printing errors. The right to delivery is reserved. All information errors are printing errors. The right to delivery is reserved. All information errors are printing errors are printing errors. The right to delivery is reserved. All information errors are printing errors ar